

111-25500



Article Number: 111-25500

Description: Heavy-Duty Cable Tie, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Base Data	Local Order Number	T255S0HIRX2
	Type	T255S
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Heavy-Duty Cable Tie, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		1115.0N
Length L (Imperial)		8.9"
Length L (Metric)		225.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Variant		Inside Serrated
Width W (Imperial)		0.5"
Width W (Metric)		12.6mm
Bundle Diameter Min. (Imperial)		0.49"
Bundle Diameter Min. (Metric)		12.5mm
Bundle Diameter Max. (Imperial)		2.2"
Bundle Diameter Max. (Metric)		55.0mm

111-25500



Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987